

## TECHNICAL DATA SHEET

**Grade:** Scrolljet 904

**g/m<sup>2</sup>:** 175

**Characteristics:**

- Inkjet coated wet strength paper, specially developed for real solvent and UV curable inks

**Applications:**

- Scrolling megalight systems
- Roll-up systems
- Photorealistic posters and prints

**Advantages:**

- High tear-resistance
- Vibrant colours day and night
- Homogeneous formation
- Environmental-friendly and recyclable

**Suitable ink systems:**

|                          |                          |                          |                          |                                     |                                     |
|--------------------------|--------------------------|--------------------------|--------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| dye                      | pigmented                | eco solvent              | mild solvent             | hard solvent                        | UV curable                          |

**Availability:** Plotter reels  
175 g/m<sup>2</sup>

| Width Zoll | Length Yds. | Width cm | Length m | Core Zoll | Qty rolls / pallet |
|------------|-------------|----------|----------|-----------|--------------------|
| 54         | 67          | 137.2    | 61       | 3"        | 24                 |
| 63.7       | 67          | 162.0    | 61       | 3"        | 24                 |

Other sizes available upon request.

### Specifications:

| Target values at 23°C / 50% r.H. for General guidance only | Methods      | Units            |       |
|--|--------------|------------------|-------|
| Substance  | DIN ISO 536  | g/m <sup>2</sup> | 175.0 |
| Thickness  | DIN 53105 T1 | µm               | 217.0 |
| L* WS  | DIN 6174     |                  | 93.5  |
| a* WS  | DIN 6174     |                  | 1.4   |
| b* WS  | DIN 6174     |                  | -7.7  |

The paper should be fed into the inkjet printer according to the printer instructions for use .The paper should be protected from moisture. Avoid marking the paper with fingerprints. A relative humidity of over 60% can affect the picture quality. Printouts with pigmented inks should be protected from smudging for a short time until the pigments have completely anchored themselves in the coating layer.

Edition: April 09

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cham Paper Group guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.